

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Product Name:	POR-15 Fuel Preservative/Stabilizer	
Product Use/Restriction:	Preservative	
Manufacturer Name:	POR-15, Inc.	Importer – Permanent Painted Coatings
Address:	P.O. Box 1235 Morristown, NJ 07962-1235	Unit 1 / 4 Prosperity Parade Warriewood, NSW, 2102
General Phone Number:	800-457-6715	(02) 9999 0122
Customer Service Phone Number:	973-887-1999	(02) 9999 0122
Technical Product Information:	800-457-6715	(02) 9999 0122
Emergency Phone Number:	1-800-457-6715	0400119210
MSDS Format:	ANSI	

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent	EC Num.
		- by weight	

SECTION 3 - HAZARDS IDENTIFICATION

Route of Exposure:	
Potential Health Effects:	Overexposure Effects: Eye irritation, skin irritation, skin irritation, headache, nausea, dizziness.
Eye:	
Skin:	
Inhalation:	
Ingestion:	
Chronic Health Effects:	
Signs/Symptoms:	
Target Organs:	
Aggravation of Pre-Existing Conditions:	

SECTION 4 - FIRST AID MEASURES

Eye Contact:	Immediately flush eyes with plenty of water for 15 to 20 minutes occasionally lifting eyelids. Get medical attention, if irritation or symptoms of overexposure persists.
Skin Contact:	Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists. Wash contaminated clothing thoroughly before re-use.
Inhalation:	If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention if necessary.
Ingestion:	If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.
Note to Physicians:	
Other First Aid:	

SECTION 5 - FIRE FIGHTING MEASURES

Flammable Properties:	Combustible liquid. At elevated temperatures, vapors can form an ignitable mixture with air. Vapors can flow along surfaces to distant ignition sources and flash back.
Flash Point:	62.8°C (145°F)
Flash Point Method:	ASTM D56
Auto Ignition Temperature:	
Lower Flammable/Explosive Limit:	
Upper Flammable/Explosive Limit:	
Fire Fighting Instructions:	
Extinguishing Media:	Dry chemical (e.g. monoammonium phosphate, potassium sulfate, and potassium chloride), carbon dioxide, high expansion (proteinic) chemical foam, sand.
Unsuitable Media:	
Protective Equipment:	As in any fire wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.
Unusual Fire Hazards:	None; Combustible, keep from source of ignition.
Hazardous Combustion Byproducts:	

## SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personnel Precautions:	
Environmental Precautions:	
Spill Cleanup Measures:	Contain liquid, keep from ignition source. Utilize absorbent material. Do not flush into sewer system.
Other Precautions:	

## SECTION 7 - HANDLING and STORAGE

Handling:	Avoid inhalation, skin contact.
Storage:	No special precautions; try to keep cool & dry.
Work Practices:	
Special Handling Procedures:	
Hygiene Practices:	

## SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

Engineering Controls:	Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Localized mechanical exhaust is normally sufficient.
Eye/Face Protection:	Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166. Contact lenses should not be worn.
Skin Protection Description:	Cover as much of the exposed skin area as possible with appropriate clothing. If skin creams are used, keep the area covered to a minimum. & dbo_Section8.HandProtectionDescription
Respiratory Protection:	A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, spray painting, or any other circumstances where air purifying respirators may not provide adequate protection.
Other Protective:	Eyewash and deluge shower should be available.

EXPOSURE GUIDELINES	
---------------------	--

--

Notes :	
---------	--

SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

Flash Point:	62.8°C (145°F)
Flash Point Method:	ASTM D56
Auto Ignition Temperature:	

SECTION 10 - STABILITY and REACTIVITY

Chemical Stability:	Stable
Reactivity:	
Hazardous Polymerization:	
Conditions to Avoid:	
Incompatible Materials:	Strong oxidizers, strong acids, oxygen
Special Decomposition Products:	

--

SECTION 11 - TOXICOLOGICAL INFORMATION

--

--

--

SECTION 12 - ECOLOGICAL INFORMATION

--

SECTION 13 - DISPOSAL CONSIDERATIONS

--

SECTION 14 - TRANSPORT INFORMATION

DOT Shipping Name:	Non-Regulated
DOT UN Number:	
DOT Hazard Class:	Non-Regulated
DOT Packing Group:	

SECTION 15 - REGULATORY INFORMATION

--

SECTION 16 - ADDITIONAL INFORMATION

--



Copyright© 1996-2010 [Actio Software Corporation](#).  
All Rights Reserved.