



# Deox—Dynax S50

ANTI-CORROSION WAX

**Permanent Painted Coatings**

## Application Information

### Product Function:

Dynax S50 is a high-performance anti-corrosion wax, that provides exceptional long-lasting protection to steel surfaces.

Dynax S50 creeps into welded seams and seals surface defects.

Dynax S50 forms a soft, brown, wax-like film that self-heals in the event of disruption.

Dynax S50 is able to arrest existing corrosion and to provide long-term protection to pre-corroded and corrosion-free surfaces.

Dynax S50 has been proven to substantially out-perform competitive material in salt-spray trials under conditions of ATM B117.

Dynax S50's soft-film is optimised for enclosed cavities where extremely corrosive conditions develop.

Dynax S50 is also recommended for protection of valuable machinery and components in transit, machine tools, moulds etc.

Dynax S50 can be removed using suitable solvent.

Dynax S50 is not formulated for prolonged exposure to ultra-violet (UV) light—please consult our technical department for recommended grade.

### How to Use:

1. Use a brush, roller or spray to apply Dynax S50.
2. Atomisation into enclosed cavities and voids is recommended to ensure thorough coverage of all surfaces. Dynax-S50 contains highly polar corrosion inhibitors that are able to displace surface moisture.
3. Dynax S50 is tolerant of a broad range of application pressures and will form coherent film upon application.
4. Dynax S50 will increase in viscosity at low storage temperatures; it is recommended to place container, or aerosols in a room at around 15°C for 24 hours prior to use.

5. For non-aerosol dispensed Dynax S50 warming the container (loosen cap first) by standing in a hot water bath will further reduce viscosity and is beneficial where deep crevice protection is required.
6. Ensure that cavities are left unclosed for a period of 48 hours to allow the escape of carrier material before bunging or stopping.
7. Dynax S50 will provide excellent protection at a wide-range of film thickness—aim to achieve a uniform dry-film thickness of around 50 microns. The tolerance of the material to maintain protection at very low film thickness makes Dynax S50 the ideal choice where surface inspection is not easy or where uniform coatings are simply not possible.

COVERAGE: 750ml can of Deox Dynax will spray a continuous mist for 5 mins.

### Technical Data:

Flash Point:	44°C
Storage:	Up to 5 years unopened.
Temp range:	+5° to 30°C
Solids:	50%
Drying Time:	24 hours (approx) @15° C
Appearance:	Brown, soft and wax-like,
Coverage:	750ml can will spray a continuous mist for 5 minutes.

The information set out in this flier is, so far as can be ascertained, true and accurate, but all recommendations or suggestions are made without guarantee.

Since the conditions of use of the Products sold by Permanent Painted Coatings Limited Permanent Painted Coatings Pty Ltd (Australia) ("PPC Pty Ltd") are beyond the control of PPC Ltd / and or PPC Pty Ltd ("the company"), the Company to the full extent allowed by law, disclaim any liability with respect to damage, injury or death consequent upon the use of the Products or consequent upon the use of the information contained herein.

The Company warrant that the Products supplied hereunder shall conform to the description or specification stated in this flier. The Company make no warranties that Products supplied are made to certain industry specifications. To the full extent allowed by law, the liability of the Company with respect to any breach of the aforesaid warranty shall be limited, at the option of the Company, to payment of the cost of replacing the Products or of acquiring equivalent products and in no case shall the Companies be liable for consequential loss or damage.

In no case will the Company be liable to defend or pay any award of damages assessed against the buyer in any suit or cause of action alleging that the use of the Products supplied hereunder infringe any patent. The Company hereby expressly disclaim any written or unwritten, express or implied representation, warranty or condition against infringement of any patent with respect to such goods.

Imported and distributed by;  
**PERMANENT PAINTED COATINGS PTY LTD**  
1/4 Prosperity Parade, Warriewood, NSW 2102.

For your nearest retail outlet  
PHONE FREE 1-800 643 229; PHONE: 02 9999 0122;

Website: [www.por15.com.au](http://www.por15.com.au)  
Email: [sales@ppcco.au.com](mailto:sales@ppcco.au.com)

