



FUEL PRESERVATIVE / STABILISER

30ML TO 10 LITRES

Application Information

PRODUCT DESCRIPTION:

POR-15 Fuel Preservative & Stabilizer saves you time, money and worry. It stops a breakdown process in fuel called oxidation. When petroleum products stagnate for any long period (2 months or more), gums and varnishes are formed by the reaction of oxygen with the fuel. These undesirable by-products greatly reduce combustibility, octane value and overall fuel efficiency. Furthermore, all internal fuel system passageways, lines, nozzles, valves, jets, etc., become restricted due to these gums and varnishes, which are very tough to remove once in place.

By adding POR-15 Fuel Preservative & Stabilizer to your tank, oxygen becomes chemically isolated, thus preventing oxidation. Additional, powerful agents neutralise corrosive compounds and also prevent rust formation.

- This product is safe for use in every type of fuel system and effectively preserves fuel for more than 2 years.
- Significant benefits include quick starting, elimination of fuel system overhaul due to storage problems, and retention of original octane performance.
- Leaves no residue after combustion.
- Safe for every type of vehicle and power equipment (2 or 4 cycle).
- POR-15 Fuel Preservative/Stabiliser effectively protects any type of fuel delivery system, whether fuel injected or carburetted, petrol or diesel.
- POR-15 Fuel Preservative/Stabiliser is formulated for every type of petrol, including leaded, unleaded; Diesel and also for highly aromatic racing fuels.
- POR-15 Fuel Preservative/Stabiliser will not make bad petrol/Diesel good again, but it will prevent further deterioration the moment it is added.
- POR-15 Fuel Preservative/Stabiliser will clean your fuel system quickly if added at **triple dosage to one tank full of gas only**, then consumed through normal engine operation. This cleaning action is accomplished without the use of solvents, which most other products contain.

- POR-15 Fuel Preservative / Stabilizer does not contain any alcohols.

DIRECTIONS:

- Open the container slowly to avoid a pressure release, which may occasionally occur at high altitudes. Point the container away from your face when opening.

ADD: 30 mls (1 oz.) to each 11.4 litres of fuel (3 gallons) 25mls to 10 litres

To use the squeeze and pour bottle:

1. Remove cap and seal from 1 oz. dispensing changer.
 2. Squeeze bottle to fill chamber to desired amount.
 3. Pour. Only measured amount will be released.
- **Make Sure** POR-15 Fuel Preservative/Stabilizer is mixed thoroughly in the tank; then operate engine for 5 to 10 minutes so that the treated fuel can travel through the fuel lines and carburettor.

The information set out in this flier is, so far as can be ascertained, true and accurate, but all recommendations or suggestions are made without guarantee. Since the conditions of use of the Products sold by Permanent Painted Coatings Pty Ltd (Australia) ("PPC Pty Ltd") are beyond the control of PPC Ltd / and or PPC Pty Ltd ("the company"), the Company to the full extent allowed by law, disclaim any liability with respect to damage, injury or death consequent upon the use of the Products or consequent upon the use of the information contained herein. The Company warrant that the Products supplied hereunder shall conform to the description or specification stated in this flier. The Company make no warranties that Products supplied are made to certain industry specifications. To the full extent allowed by law, the liability of the Company with respect to any breach of the aforesaid warranty shall be limited, at the option of the Company, to payment of the cost of replacing the Products or of acquiring equivalent products and in no case shall the Company be liable for consequential loss or damage. In no case will the Company be liable to defend or pay any award of damages assessed against the buyer in any suit or cause of action alleging that the use of the Products supplied hereunder infringe any patent. The Company hereby expressly disclaim any written or unwritten, express or implied representation, warranty or condition against infringement of any patent with respect to such goods.

PERMANENT PAINTED COATINGS PTY LTD
1/4 Prosperity Parade Warriewood, NSW 2102.
PHONE FREE 1800 643 229
Phone 02 9999 0122
Fax 02 9999 0394
EMAIL: sales@ppcco.com.au
Website: www.por15.com.au

