



Permanent Painted Coatings

SW2 PROTECTIVE OIL

Application Information

PRODUCT DESCRIPTION

SW 2 Protective Oil is similar to fish oil, (but a chemical version) without the smell and with excellent penetrating ability. It's able to penetrate into difficult to get to areas, where applying paints like POR 15 Rust Preventive Paint or similar are hard or impossible. It has an excellent capillary action and spreads into all cracks and folds.

SW2 forms a hard, water resistant film and is useful in protecting steel from condensation corrosion, as encountered in particular on:

- USES:
- Interior of vehicle doors and body panels; chassis hollow sections or trapped recesses.
 - Underside of surfaces on appliances, such as freezers and washing machines
 - Marine topsides. Engine room appliances

SW2 can also be used as a long term protective film for stored machined parts, casting etc. (SW2 should be mechanically removed or stripped before use.). Marine Clean or GP thinners will do this. Excellent at protecting metal during metal item assembly to prevent rust.

- **Not to be used as a lubricating oil**
- **Not recommended for immersion**

FEATURES:

Thin penetrating liquid which dries to a non tack film

- Water resistant
- Anti-corrosive
- Can be overcoated with many paints
- Easy application
- Lead and chromate free

PRODUCT CHARACTERISTICS

Coating Type: Oil Based

VOC: 610g per litre

Colour: Clear

Density: 0.90kg per litre

Packaging: Single Component

Temperature Resistance: 80°C dry

Sizing: 500mls, 1 litre and 4 litres

Volume Solids: 30%

Gloss: Satin

Thinner: POR15 Thinner

Application: Brush or spray

Theoretical Coverage: 30 sqm/lt at 10 microns DFT

Recommended Film Thickness Per Coat: 33 microns wet to obtain 10 microns dry

Dry Times (at 25°C): Touch Dry - 4 Hours; To Recoat - Overnight

Storage: Store under cool, dry conditions

SURFACE PREPARATION

- All surfaces must be free of oil, grease, dirt, all loose corrosion and unsound coatings.
 - Where mechanical parts are to be protected by SW 2, surfaces must be dry and free of oil and grease.
1. Power Tool clean to SSPC SP3
 2. Hand tool clean to SSPC SP2

MIXING AND THINNING

- SW2 does not require thinning or mixing. Use POR15 or GP Thinners for clean up.

APPLICATION

- Method - brush, trigger spray, pressure spray, or wipe on with clean lint free cotton cloth.
- Where topcoating SW2 with other paints, only apply enough SW2 to wet surface. Excess should be removed by wiping off with clean lint free cloth.

The information set out in this flier is, so far as can be ascertained, true and accurate, but all recommendations or suggestions are made without guarantee.

Since the conditions of use of the Products sold by Permanent Painted Coatings Pty Ltd (Australia) ("PPC Pty Ltd") are beyond the control of PPC Ltd / and or PPC Pty Ltd ("the company"), the Company to the full extent allowed by law, disclaim any liability with respect to damage, injury or death consequent upon the use of the Products or consequent upon the use of the information contained herein.

The Company warrant that the Products supplied hereunder shall conform to the description or specification stated in this flier. The Company make no warranties that Products supplied are made to certain industry specifications. To the full extent allowed by law, the liability of the Company with respect to any breach of the aforesaid warranty shall be limited, at the option of the Company, to payment of the cost of replacing the Products or of acquiring equivalent products and in no case shall the Company be liable for consequential loss or damage.

In no case will the Company be liable to defend or pay any award of damages assessed against the buyer in any suit or cause of action alleging that the use of the Products supplied hereunder infringe any patent. The Company hereby expressly disclaim any written or unwritten, express or implied representation, warranty or condition against infringement of any patent with respect to such goods.

PERMANENT PAINTED COATINGS LTD

Unit 1 / 4 Prosperity Parade;
WARRIEWOOD
NSW 2102

Phone free: 1-800 643 229

Telephone: 02 9999 0122

Fax: 02 9999 0394

Website: www.por15.com.au

E Mail: sales@ppcco.com.au



Permanent Painted Coatings

