

SAFETY DATA SHEET

Underhood Matte Black

SECTION 1 - IDENTIFICATION

Product Identifier

Product Number(s) 12032Z
 Product Name Underhood Matte Black - 12032Z

Other Means of Identification None

Recommended Use and Restrictions on Use

Recommended Use Rust preventative
 Restrictions on Use None Identified

**24 hr Emergency
Phone Number**

**800-255-3924
(Chem-Tel)**

SUPPLIER DETAILS

Name The Eastwood Company
 Address 263 Shoemaker Road
 Pottstown PA 19464
 Phone Number 610-323-2200
 Fax Number 610-323-6268

Australian Supplier:
 Permanent Painted Coatings
 Unit 1 / 4 Prosperity Parade
 WARRIEWOOD NSW 2102
 (02) 9999 0122

SECTION 2 - IDENTIFICATION

Hazard Classification

HEALTH HAZARDS				PHYSICAL HAZARDS					
Acute Tox. Oral	<input type="checkbox"/>	Mutagenicity	<input type="checkbox"/>	Unstable Explosive	<input type="checkbox"/>	Refrigerated Liq. Gas	<input type="checkbox"/>	Pyrophoric Solid	<input type="checkbox"/>
Acute Tox. Skin	<input type="checkbox"/>	Carcinogenicity	2	Explosive	<input type="checkbox"/>	Flammable Liquid	<input type="checkbox"/>	Emits Flammable Gas	<input type="checkbox"/>
Acute Tox. Inhalation	<input type="checkbox"/>	Tox. to Reproduction	2	Flammable Gas	<input type="checkbox"/>	Flammable Solid	<input type="checkbox"/>	Oxidizing Liquid	<input type="checkbox"/>
Skin Irritation	<input type="checkbox"/>	STOT SE	3	Aerosol	1	Self-Reactive Sub.	<input type="checkbox"/>	Oxidizing Solid	<input type="checkbox"/>
Eye Irritation	2	STOT RE	2	Oxidizing Gas	<input type="checkbox"/>	Pyrophoric Liquid	<input type="checkbox"/>	Organic Peroxide	<input type="checkbox"/>
Resp. Sensitization	<input type="checkbox"/>	Aspiration Hazard	1	Gas Under Pressure	X	Self-Heating Substance	<input type="checkbox"/>	Corrosive to Metal	<input type="checkbox"/>
Skin Sensitization	<input type="checkbox"/>		<input type="checkbox"/>	ENVIRONMENTAL HAZARDS (GHS Rev 3 Only)					
	<input type="checkbox"/>		<input type="checkbox"/>	Aquatic Acute	<input type="checkbox"/>	Aquatic Chronic	<input type="checkbox"/>	Ozone Depleting	<input type="checkbox"/>

Signal Word

Danger

Hazard Pictograms

Hazard Statements

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements

General Keep out of reach of children.

Prevention Obtain special instructions before use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe dust/fume/gas/mist/vapours/spray. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

SAFETY DATA SHEET

Underhood Matte Black

Part No. 120327 Aerosol

August 18, 2019

Revision 2

Page 2 of 9

Response	<i>IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER or doctor if you feel unwell.</i>
Storage	<i>Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.</i>
Disposal	<i>Dispose of contents/container in accordance with local regulations.</i>
Hazards Not Otherwise Classified	<i>None identified.</i>
Unknown Acute Toxicity	<i>12 % by wt</i>

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

ID	INGREDIENT	CAS NUMBER	% WT RANGE*
1	Acetone	0000067-64-1	15 - 40
2	Propane	0000074-98-6	15 - 40
3	Ethyl Acetate	0000141-78-6	10 - 30
4	Toluene	0000108-88-3	5 - 10
5	C9-15 Heavy Aromatic Hydrocarbon	0064742-94-5	5 - 10
6	Propylene Glycol Mono Methyl Ether Acetate	0000108-65-6	3 - 7
7	Methyl Acetate	0000079-20-9	1 - 5
8	Xylene	0001330-20-7	1 - 5
9	Amorphous Silica, Precipitated	0112926-00-8	1 - 5
10	Carbon Black	0001333-86-4	0.5 - 1.5
11	Ethyl Benzene	0000100-41-4	0.1 - 1

* Exact percentages of composition withheld as trade secret

SECTION 4 - FIRST AID MEASURES

Description of First-Aid Measures

General	<i>If exposed or concerned seek medical advice/attention.</i>
Eye Contact	<i>Immediately flush with clear water for at least 15 minutes, including under the eyelids. Consult a doctor.</i>
Skin Contact	<i>Remove with soap and water, rinsing and repeating for 15 minutes. Use skin cream to counter any resulting dryness. Consult a physician if irritation continues. If large skin area is affected, remove contaminated clothing.</i>
Ingestion	<i>Do not induce vomiting! Immediately have the victim drink plenty of water. Do not give milk or digestible oils. Keep airways free. Contact a physician. Never give anything by mouth if victim is rapidly losing consciousness, unconscious, or convulsing.</i>
Inhalation	<i>Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if symptoms persist or if unconscious.</i>
First-Aid Responder Protection	<i>Wear adequate personal protective equipment based on the nature and severity of the emergency.</i>

Most Important Symptoms and Effects, Both Acute and Delayed

Eye Contact	<i>Liquid contact may cause pain along with moderate eye irritation.</i>
Skin Contact	<i>Prolonged or repeated exposure may cause skin irritation. Repeated contact may cause drying or flaking of skin. May cause more severe response if confined to skin.</i>
Ingestion	<i>Due to being an aerosol, the product does not lend itself to ingestion. Should ingestion occur, it may cause irritation to membranes of the mouth, throat, and gastrointestinal tract resulting in vomiting and/or cramps. Aspiration of vomit into the lungs may cause inflammation, and possible chemical pneumonitis, bronchopneumonia, or pulmonary edema.</i>
Inhalation	<i>Prolonged or repeated overexposure is anesthetic. May cause irritation of the respiratory tract, or acute nervous system depression characterized by headache, dizziness, staggering gait, confusion or death. Irritation of the mucous membranes, coughing, and dyspnea are also possible.</i>

Indication of Immediate Medical Attention and Special Treatment

Notes to Physician	<i>Treat symptomatically.</i>
Specific Treatments/Antidotes	<i>No information available.</i>

SAFETY DATA SHEET

Underhood Matte Black

Part No. 120327 Aerosol

August 18, 2015

Revision 2

Page 3 of 9

Immediate Medical Attention *No information available.*

SECTION 5 - FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media *Water, CO₂, dry chemical, or universal aqueous film forming foam*

Unsuitable Extinguishing Media *Water jet*

Specific Hazards Arising from the Chemical or Mixture

Decomposition Products *Oxides of carbon (CO, CO₂), smoke, and/or vapors*

Hazards from the Product *CONTENTS EXTREMELY FLAMMABLE AND UNDER PRESSURE. In a fire or if heated, a pressure increase will occur which may result in the container bursting. Vapors heavier than air may spread along the ground and travel to an ignition source.*

Advice for Firefighters

Protective Actions *Use water spray to cool fire exposed containers as contents may rupture violently from heat developed pressure.*

Protective Equipment *As with any fire wear SCBA pressure-demand, MSHA/NIOSH approved, and full protective gear.*

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

For Non-Emergency Personnel *No action should be taken by non-emergency personnel without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spill. Remove ignition sources and provide adequate ventilation only if it is safe to do so.*

For Emergency Responders *Use personal protection as recommended in Section 8. Observe precautions provided for non-emergency personnel.*

Environmental Precautions

Precautions *Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.*

Methods and Materials for Containment and Cleaning Up

Containment Procedures *Product is an aerosol, therefore spills and leaks are unlikely. In case of rupture, released content may be contained with oil/solvent absorbent pads, socks, and/or absorbents. DO NOT use combustible material such as sawdust.*

Cleanup Procedures *Spills from aerosol cans are unlikely and are generally of small volume. Large spills are therefore not normally considered a problem. In case of actual rupture, avoid breathing vapors and ventilate area well. Remove sources of ignition and use non-sparking equipment. Soak up material with inert absorbent and place in safety containers for proper disposal.*

Other Information *Aerosol products represent a limited hazard and will not spill or leak unless ruptured. In case of rupture contents are generally evacuated from the can rapidly. Area should be ventilated immediately and continuous ventilation provided until all fumes and vapors have been removed. Aerosol cans should never be incinerated or burned. See Section 13 for disposal.*

Prohibited Materials *Combustible absorbent material such as sawdust, use of equipment that may cause sparking.*

SECTION 7 - HANDLING AND STORAGE

Precautions for Safe Handling

General Handling Precautions *KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged or repeated skin contact. Avoid breathing of vapors. Do not incinerate (burn) containers. Always replace overcap when not in use. Avoid use around open flames or other sources of ignition. Exposure to heat or prolonged exposure to sun may cause can to burst. Use only with adequate ventilation, opening doors or windows to achieve cross-ventilation. Wash hands after use.*

Hygiene Recommendations *Do not eat, drink or smoke when using this product. Wash hands thoroughly after use. Remove contaminated clothing and protective equipment before entering eating or smoking areas.*

SAFETY DATA SHEET

Underhood Matte Black

Part No. 120327 Aerosol

August 18, 2019

Revision 2

Page 4 of 9

Conditions for Safe Storage Including Any Incompatibilities

- Storage Requirements** *Storage of individual cans should be done in an area below 50 °C (122 °F), and away from heat sources. Ensure can is in a secure place to prevent knocking over and accidental rupture. For storage of pallet quantities, compliance with NFPA 30B (Manufacture and Storage of Aerosol Products) is recommended. This product is classified as a Level 3 Aerosol.*
- Incompatibilities** *Segregate storage away from materials indicated in Section 10*

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters

Occupational Exposure Limits

ID	PEL	OSHA STEL	CEILING	IDLH	REL	NIC SH	STEL	CEILING	TLV	ACGIH STEL	CEILING	AIHA WEEL
1	1000 ppm	–	–	2500 ppm	250 ppm	–	–	–	500 ppm	750 ppm	–	–
2	1000 ppm	–	–	2100 ppm	1000 ppm	–	–	–	1000 ppm	–	–	–
3	400 ppm	–	–	2000 ppm	400 ppm	–	–	–	400 ppm	–	–	–
4	200 ppm	–	300 ppm	500 ppm	100 ppm	150 ppm	–	–	50 ppm	–	–	–
7	200 ppm	–	–	3100 ppm	200 ppm	250 ppm	–	–	200 ppm	250 ppm	–	–
8	100 ppm	–	–	900 ppm	100 ppm	150 ppm	–	–	100 ppm	150 ppm	–	–
9	20 mppcf	–	–	3000 mg/m3	6 mg/m3	–	–	–	–	–	–	–
10	3.5 mg/m3	–	–	1750 mg/m3	3.5 mg/m3	–	–	–	3 mg/m3	–	–	–
11	100 ppm	–	–	800 ppm	100 ppm	125 ppm	–	–	20 ppm	–	–	–

Biological Exposure Indices

ID	DETERMINANT	SAMPLING TIME	BEI	NOTATION
1	Acetone in urine	End of shift	50 mg/L	Ns
4	o-Cresol in urine	End of shift	0.5 mg/L	B
8	Methylhippuric acids in urine	End of shift	1.5 g/g creatinine	–
11	Sum of mandelic acid and phenyl glyoxylic acid in urine	End of shift at end of workweek	0.7 g/g creatinine	Ns, Sq

Other Control Parameters *Not Available*

Appropriate Engineering Control

Engineering Measures *Use only with adequate ventilation. General ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Local exhaust ventilation or an enclosed handling system may be necessary to control air contamination below that of the lowest OEL from the table above.*

Individual Protection Measures

- Hygiene Considerations** *Avoid breathing vapors and contact with the skin and eyes. Always replace overcap when not in use. Keep out the reach of children. Wash hands after use.*
- Thermal Protection** *This product does not present a thermal hazard.*
- Respiratory Protection** *An approved respirator with organic vapor cartridge may be permissible under certain circumstances where airborne concentrations are expected to exceed occupational exposure limits. If respirators are needed, compliance with OSHA standard 29 CFR 1910.134 is necessary.*
- Skin Protection** *For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or repeated contact could occur, use protective clothing impervious to the ingredients listed in Section 2.*
- Eye/Face Protection** *Safety glasses with side shields are recommended as a minimum for any type of industrial chemical handling. Where eye contact with this material could occur, chemical splash proof goggles are recommended.*
- Other Protective Equipment** *Safety showers and eye-wash stations should be available in the workplace near where the material will be used.*

SAFETY DATA SHEET

Underhood Matte Black

Part No. 120327 Aerosol

August 18, 2019

Revision 2

Page 5 of 9

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical Properties

Boiling Point	> 56.1 °C (133.0 °F)	Melting / Freezing Point	> -98.1 °C (-144.6 °F)
Flash Point, Liquid	> -17.0 °C (1.4 °F)	Flash Point, Propellant	-104.4 °C (-156.0 °F)
Explosive Limits	0.85% - 24.60%	Autoignition Temperature, Liquid	227.8 °C (442.0 °F)
Flammability	Extremely Flammable Aerosol	Relative Density (H2O = 1)	0.746 g/cc
Molecular Weight	Not Available	Weight	6.222 lbs/gal
Vapor Pressure	108.00 psig	pH	Not Available
Vapor Density	5.580 g/cc Maximum	Evaporation Rate	Not Available
Form	Pressurized Product	Partition Coefficient	Not Available
Viscosity	Not Available	Refractive Index	Not Available
Odor Threshold	Not Available	Heat of Combustion (L.H.C)	Not Available
Odor	Paint-like	Water Solubility	Not Available
Appearance / Color	Black color	Decomposition Temperature	Not Available

Air Quality Properties

Percent Volatile	88% Wt (92% Vol) Max	VOC Regulatory	5.03 lbs/gal (602.785 g/L)
Percent VOC	61% Wt (67% Vol) Max	VOC Actual	3.776 lbs/gal (452.409 g/L)
Percent HAP	11% Wt (9% Vol) Max	HAP Content	0.631 lbs/gal (75.607 g/L)
Solids/Non Volatile Content	13% Wt (9% Vol) Max	Maximum Incremental Reactivity	1.381 g O3/g
Global Warming Potential	1.165		

SECTION 10 - STABILITY AND REACTIVITY

Reactivity

No specific test data related to reactivity is available for this product or its ingredients.

Chemical Stability

This product is stable.

Hazardous Reactions

Under normal conditions of storage and use, hazardous reactions are not expected to occur.

Conditions to Avoid

Keep away from heat, sparks, flame, and red hot metal.

Material Incompatibility

Acids, Activated Carbon, Alkali Metals, Alkalis, Aluminum, Bases, Copper, Dichlorohydrantion, Halogens, Hexachloromelamine, Hydrofluoric Acid, Hydrogen Peroxide, Isoprene, Lithium Aluminum Hydride, Manganese Trifluoride, Nitrates, Nitric Acid, Nitrogen Tetroxide, Potassium Tert-Butoxide, Silver Perchlorate, Strong Acids, Strong Oxidizing Agents, Strong Reducing Agents, Sulfur Dichloride, Tetranitromethane, Trichloromelamine, Uranium Hexafluoride

Decomposition Productions

Oxides of Carbon, Acetic Acid, Formaldehyde fumes, Hydrogen Peroxide, Isoproanol, Methanol may be formed depending on fire conditions.

SECTION 11 - TOXICOLOGICAL INFORMATION

Acute Toxicity Estimates (mixture)

Oral LD ₅₀	2909 mg/kg
Dermal LD ₅₀	9571 mg/kg
Inhalation LC ₅₀	47 mg/L 4-hour

SAFETY DATA SHEET

Part No. 120322 Aerosol

August 18, 2015

Revision 2

Page 6 of 9

Underhood Matte Black

Acute Toxicity on Ingredients

ID	ORAL LD50		DERMAL LD50		INHALATION LC50		
	VALUE	SPECIES	VALUE	SPECIES	VALUE	TIME	SPECIES
1	5800 mg/kg	rat	20000 mg/kg	rabbit	76 mg/m3	4h	rat
2	–	–	–	–	658 mg/L	4h	rat
3	10200 mg/kg	rat	>18000 mg/kg	rabbit	>32380 ppm	4h	rat
4	636 mg/kg	rat	>12000 mg/kg	rabbit	49 mg/m3	4h	rat
5	–	–	>3160 mg/kg	rabbit	>11.4 mg/L	6h	rat
6	8532 mg/kg	rat	7500 mg/kg	rabbit	>5320 ppm	4h	rat
7	>5000 mg/kg	rat	>5000 mg/kg	rat	>16000 mg/L	4h	rat
8	4300 mg/kg	rat	4500 mg/kg	rabbit	6700 mg/L	4h	rat
10	>15400 mg/kg	rat	>3000 mg/kg	rabbit	6750 mg/m3	4h	rat
11	4720 mng/kg	rat	15500 mg/kg	rabbit	4000 ppm	4h	rat

Health Hazard Classification

Skin Corrosion / Irritation	<i>Classification criteria not met</i>
Eye Damage / Irritation	<i>Category 2</i>
Respiratory Irritation	<i>Classification criteria not met</i>
Respiratory / Skin Sensitization	<i>Classification criteria not met</i>
Germ Cell Mutagenicity	<i>Classification criteria not met</i>
Reproductive Toxicity	<i>Category 2</i>
STOT - Single Exposure	<i>Category 3</i>
STOT - Repeated Exposure	<i>Category 2</i>
Aspiration Hazard	<i>Category 1</i>

Carcinogen Data

ID	Calif Prop-65	OSHA	NIOSH	ACGIH	NTP	IARC
10	Yes	–	App A & C	A3	–	2B
11	Yes	–	–	A3	–	2B

Information on the Likely Routes of Exposure

Routes of Exposure *Skin contact, skin absorption, eye contact, inhalation*

Information on Physical, Chemical and Toxicological Effects

Symptoms of Exposure *Abdominal Cramps, Asphyxia, Central Nervous System Depression, Chest Tightness, Coma, Confusion, Cough, Dermatitis, Diarrhoea, Dizziness, Drowsiness, Dry Cracking Skin, Excitation, Optic Nerve Atrophy, Skin Irritation, Staggering Gait, Throat Irritation, Vomiting*

Delayed and Immediate Effects and also Chronic Effects from Short and Long-Term Exposure

Delayed Effects *No known delayed effects.*

Immediate Effects *No known immediate effects.*

Chronic Effects *Reports have associated repeated and prolonged occupational overexposure to solvents with irreversible brain and nervous system damage (sometimes referred to as "Solvent or Painter's Syndrome"). Intentional misuse by concentrating and inhaling this product may be harmful or fatal. Reports of chronic poisoning from Toluene describe anemia, decreased blood cell count and bone marrow hypoplasia. Liver and kidney damage may occur. Exposure may affect a developing fetus.*

Medical Conditions Aggravated *May aggravate personnel with pre-existing disorders associated with any of the Target Organs.*

Target Organs *Bladder, Blood, Central Nervous System, Eyes, Gastrointestinal Tract, Kidneys, Liver, Respiratory System, Skin*

SAFETY DATA SHEET

Underhood Matte Black

Part No. 120324 Aerosol

August 18, 2019

Revision 2

Page 7 of 9

SECTION 12 - ECOLOGICAL INFORMATION

Acute Aquatic Toxicity

ID	TYPE	FISH VALUE	PERIOD	TYPE	INVERTEBRATES VALUE	PERIOD	TYPE	AQUATIC PLANTS VALUE	PERIOD	TYPE	MICROORGANISMS VALUE	PERIOD
1	LC50	5549 mg/L	96h	EC50	6100 mg/L	48h	IC5	530 mg/L	8d	EC5	1700 mg/L	16h
3	LC50	230 mg/L	96h	EC50	717 mg/L	48h	EC50	3300 mg/L	48h	EC50	5870 mg/L	15m
4	LC50	13 mg/L	96h	EC50	11.5 mg/L	48h	EC50	>250 mg/L	24h	ECO	29 mg/L	16h
5	LC50	45 mg/L	96h	-	-	-	-	-	-	-	-	-
6	LC50	180 mg/L	96h	EC50	408 mg/L	48h	IC50	>1000 mg/L	72h	EC20	>1000 mg/L	30m
7	LC50	399 mg/L	96h	EC50	1027 mg/L	48h	EC50	>120 mg/L	72h	EC50	6100 mg/L	30m
8	LC50	26.7 mg/L	96h	LC50	14 mg/L	24h	-	-	-	-	-	-
9	-	-	-	EC50	>1000 mg/L	96h	-	-	-	-	-	-
10	NOEC	1000 mg/L	96h	EC50	>5600 mg/L	24h	-	-	-	ECO	400 mg/L	3h
11	LC50	97.1 mg/L	96h	LC50	77 mg/L	24h	EC50	63 mg/L	3h	EC50	130 mg/L	48h

Ecological Data

ID	PERSISTENCE	PERSISTENCE AND DEGRADABILITY BOD	COD	ThOD	BIOACCUMULATIVE POTENTIAL Pow / Kow	BCF	MOBILITY Koc
1	90.9% / 28 days	1.85 mg/g / 5d	1.92 mg/L	2.21 mg/L	-0.24 log BCF	0.69 BCF	1.26 log BCF
2	-	-	-	-	2.36 log BCF	1.47 log BCF	2.36 log BCF
3	100% / 28 days	1 g/g	1.69 g/g	1.82 g/g	0.73 log BCF	1.48 log BCF	0.788 log BCF
4	86% / 20 days	2.15 mg/g	2.52 mg/g	3.13 mg/g	2.65 BCF	1.57 log BCF	2.15 log BCF
6	-	360 mg/g	1740 mg/g	1820 mg/g	0.56 log BCF	0.01 log BCF	0.36 log BCF
7	-	-	1511.8 mg/g	1510 mg/g	0.18 log BCF	-	0.68 log BCF
8	-	0.64 mg/L	-	2410 mg/g	3.271 log BCF	2.2557 log BCF	3.156 log Koc
10	-	5 mg/L	-	-	1.09 log BCF	0.599 log BCF	1.99 log Koc
11	-	1780 mg/g	-	3170 mg/g	3.15 log BCF	1.18 log BCF	2.4 log Koc

Other Adverse Effects

No additional information available.

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal

Characteristics and waste stream classification can change with product use and location. It is the responsibility of the user to determine the proper storage, transportation, treatment, and/or disposal methodologies for spent materials and residues at the time of disposition. All waste must be disposed of in compliance with the respective national, federal, state, and/or local regulations.

Waste Disposal of Packaging

An aerosol container that does not contain a significant amount of liquid would meet the definition of scrap metal (40 CFR 261.1(c)(6)), and would be exempt from RCRA regulation under 40 CFR 261.6(a)(3)(iv) if it is to be recycled. If containers are to be disposed of (not recycled) it must be managed under all applicable RCRA and state regulations.

Landfill Precautions

Not available

Incineration Precautions

**** DO NOT INCINERATE ** CONTENTS UNDER PRESSURE ****

SAFETY DATA SHEET

Underhood Matte Black

Part No. 120327 aerosol

August 18, 2015

Revision 2

Page 8 of 9

SECTION 14 - TRANSPORTATION INFORMATION

Transportation Information

UN Number
Proper Shipping Name
Hazard Class(es)
Packaging Group
Marine Pollutant
Hazard Label(s)

Ground Transportation (DOT)

UN1950
Aerosols, Limited Quantity
2.1
—
No

Air Transportation (IATA)

UN1950
Aerosols, Flammable, Limited Quantity
2.1
—
No

Ocean Transportation (IMDG)

UN1950
Aerosols, Limited Quantity
2.1
—
No



SECTION 15 - REGULATORY INFORMATION

Federal Regulations

ID	TSCA LISTED	SARA 302 EHS TPQ	RCRA	CERCLA	SARA 313	FIRE	REACTIVITY	SARA 311/312 ACUTE	CHRONIC	PRESSURE	CLEAN AIR ACT HAP	CLEAN AIR ACT SOCMI	CLEAN WATER ACT
1	Yes	—	U002	5000	—	Yes	—	Yes	—	—	—	—	—
2	Yes	—	—	—	—	Yes	—	—	—	—	—	—	—
3	Yes	—	U112	5000	—	Yes	—	Yes	—	—	—	—	—
4	Yes	—	U220	1000	8%	Yes	—	Yes	Yes	—	Yes	Yes	1000 (PP)
5	Yes	—	—	—	—	—	—	Yes	—	—	—	—	—
6	Yes	—	—	—	—	Yes	—	—	—	—	—	—	—
7	Yes	—	—	—	—	Yes	—	Yes	—	—	—	—	—
8	Yes	—	U239	100	2%	Yes	—	Yes	—	—	Yes	Yes	100
9	Yes	—	—	—	—	—	—	—	—	—	—	—	—
10	Yes	—	—	—	—	—	—	—	—	—	—	—	—
11	Yes	—	—	1000	>1%	Yes	—	Yes	—	—	Yes	Yes	1000 (PP)

State Regulations

ID	CA P-65	DE RQ	MA RTK CODES	NE TYPE	NE RQ	RTK	MN AIR	WATER	NJ RTK	AIR	NY LAND	ACUTE	PA LISTED	WA PEL TWA	WI TABLE	WV TAP
1	—	5000	2,4,5,6 F8 F9	—	20000	AON	—	—	—	5000	1	—	Yes-E	750 ppm	—	—
2	—	F 1000 **	2,4,5,6	—	—	AP	—	—	Yes	—	—	—	Yes	1000 ppm	—	—
3	—	5000	2,4,5,6 F8	—	20000	AO	—	—	—	5000	1	—	Yes-E	400 ppm	—	—
4	DF	1000	2,4,5,6 F7 F8 F9	—	2000	ANO	Yes	Yes	Yes	1000	1	—	Yes-E	100 ppm	A	—
7	—	—	2,4,5,6	—	—	AO	—	—	—	—	—	—	Yes	200 ppm	—	—
8	—	100	2,4 F8 F9	—	2000	ANO	Yes	—	Yes	1000	1	—	Yes-E	100 ppm	A	—
9	—	—	4	—	—	—	—	—	—	—	—	—	—	6 mg/m3	—	—
10	C	—	2,4 F5	—	—	ANOR	—	—	—	—	—	—	Yes	3.5 mg/m3	A	—
11	C	100	2,4,5,6 F7 F8 F9	—	2000	AO	Yes	Yes	Yes	1000	1	—	Yes-E	100 ppm	A	—

SECTION 16 - OTHER INFORMATION

SDS Revision History

Revision 1, 09/28/2011, Original
Revision 2, 08/18/2015, Updated to GHS Version 3 Format.

SDS Compliance

This SDS complies with the below listed regulations only. For SDS that comply with other countries, please contact our Regulatory Department.

OSHA Hazard Communication Standard (HCS 2012) 29 CFR 1910.1200
Globally Harmonized System of Classification and Labeling of Chemicals (GHS) Revision 3

SAFETY DATA SHEET

Underhood Matte Black

Part No. 120327 Aerosol

August 18, 2019

Revision 2

Page 9 of 9

Disclaimer of Liability

The information contained herein is based upon data provided to us by our suppliers, and reflects our best judgement. However, no warranty of merchantability, fitness for any use, or any other warranty or guarantee is expressed or implied regarding the accuracy of such data, or the results to be obtained from use thereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, we do not assume any responsibility for the results of such application. This information is furnished upon the condition that the persons receiving it shall make their own determinations of the suitability of the material for any particular use. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist.