

MATERIAL SAFETY DATA SHEET

EW HIGH-TEMP ENGINE PAINT ASSORTED COLORS

Printed: 02/25/09

=====

Manufacturer:
THE EASTWOOD COMPANY
263 SHOEMAKER ROAD
POTTSTOWN, PA 19464
Phone: 800-345-1178

Hazard Rating:
Least --> Greatest
0 --> 4

----- HMIS CODES -----
Health 3
Flammability 3
Reactivity 2
Personal Protection J

EMERGENCY TELEPHONE: 800-424-9300

SECTION I: PRODUCT IDENTIFICATION

Product Code: 51615ZP, 51616ZP, 51617ZP, 51618ZP, 51619ZP, 51620ZP, 51621ZP,
51622ZP, 51623ZP, 51624ZP, 51626ZP, 51627ZP, 51628ZP, 51629ZP,
51630ZP, 51631ZP, 51632ZP, 51633ZP, 51634ZP
Product Name: EW HIGH-TEMP ENGINE PAINT
Product (s): EW HIGH-TEMP ENGINE PAINT
Product Class: PAINT CAS Number: NA

SECTION IIA: HAZARDOUS INGREDIENTS (To Nearest 1.00%1

INGREDIENT	Number	% by Weight	% by Volume	LEL % (V)	Vapor Pressure
1. SILICONE ALKYD	1	88.00	88.00	1.0	1.30
2. ALUMINUM	2	1.00	.42	1.0	.40
3. MIN. ?PI	3	9.00	.00	9.00	10.00
NA = Not Applicable; NE = Not Established					

SECTION IIB: OCCUPATIONAL EXPOSURE LIMITS

Ingr. #	OSHA ppm	OSHA mg/m3	TWA ppm	TWA mg/m3	STEL ppm	STEL mg/m3
1.	500.000	NA	500.000	NA	NA	NA
2.	500.000	NA	500.000	NA	NA	NA
3.	100.000	NA	100.000	100.000	100.000	NA
NA = Not Applicable; NE = Not Established						

SECTION III: PHYSICAL DATA

Boiling Range (degrees F): 282.00 - 286.00 Pounds per Gallon: 7.77
Vapor Density: HEAVIER THAN AIR Evaporation Rate: SLOWER THAN ETHER
Solubility in Water: NIL

Volatiles (%)	by Weight	by Volume
Total	45.79	52.29
Exempt VOC	.00	.00
Non-exempt	45.79	52.29

VOE wt/gal: 3.56 lbs non-exempt solvent per adjusted gallon
Appearance: Liquid, Assorted Colors

MATERIAL SAFETY DATA SHEET

EW HIGH-TEMP ENGINE PAINT ASSORTED COLORS

Printed: 02/25/09

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

Flammability Classification:

OSHA: COMB DOT: COMB

Flash Point: 105 (Method: Tee)

UEL: 7

Extinguishing Media: CO2/FOAM

Unusual Fire and Explosion Hazards

THIS MATERIAL MAY BE IGNITED BY HEAT, SPARKS, FLAME OR STATIC ELECTRICITY.
KEEP CONTAINERS CLOSED WHEN NOT IN USE. ISOLATE FROM HEAT, SPARKS, PILOT LIGHTS
SMOKING MATERIALS AND OTHER SOURCES OF IGNITION.

Special Firefighting Procedures

THE USE OF SCBA IS RECOMMENDED FOR FIRE FIGHTERS. WATER SPRAY MAY BE USEFUL IN
IN COOLING CONTAINERS EXPOSED TO HEAT AND FLAME. AVOID SPREADING BURNING
LIQUID WITH WATER USED FOR COOLING PURPOSES.
FIGHT AS VOLATILE LIQUID FIRE. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO
EXTREME HEAT. USE WATER TO COOL FIRE EXPOSED CONTAINERS.

SECTION V: HEALTH HAZARD DATA

Effects of Overexposure

DIZZINESS, NAUSEA, VOMETING, LOSS OF COORDINATION, AND FATIGUE.

Medical Conditions Prone to Aggravation by Exposure

ASTHMA, HEART CONDITION.

Primary Routes of Entry into the Body, and Effects

MOUTH, SKIN, LUNGS.

EMERGENCY FIRST-AID PROCEDURES

SKIN CONTACT: FLUSH WITH WATER, IF REDNESS PERSISTS SEEK MEDICAL ATTENTION.
INHALATION: IF RESPIRATORY SYMPTOMS DEVELOP, REMOVE VICTIM FROM SOURCE OF
EXPOSURE TO FRESH AIR. IF SYMPTOMS PERSIST SEEK MEDICAL ATTENTION
INGESTION: SEEK EMERGENCY MEDICAL ATTENTION

SECTION VI: REACTIVITY DATA

Stability: STABLE Hazardous Polymerization WILL NOT OCCUR.

Hazardous Decomposition Products

CO2

Conditions to Avoid

HEAT, SPARKS OPEN FLAMES, STATIC ELECTRICITY

Incompatibilities (Materials to Avoid)

MATERIAL SAFETY DATA SHEET

EW HIGH-TEMP ENGINE PAINT ASSORTED COLORS

Printed: 02/25/09

SECTION VII: SPILL OR LEAK PROCEDURES: WASTE DISPOSAL

Steps to be taken if Material is Leaked or Spilled
STAY UPWIND. REMOVE SOURCE OF IGNITION. KEEP OUT OF DRAINS SEWERS, WATERWAYS
USE ABSORBANT PADS

Waste Disposal Methods

DISPOSE PRODUCT IN ACCORDANCE WITH LOCAL, COUNTY STATE, AND FEDERAL REGULATIONS.

SECTION VIII: SAFE HANDLING AND USE INFORMATION

Respiratory Protection

APPROVED ORGANIC SUPPLIED AIR RESPIRATOR

Ventilation

MECHANICAL EXPLOSIONPROOF

Protective Gloves

YES

Eye Protection

YES

Other Protective Equipment

IMPERVIOUS CLOTHING

Hygienic Practices

WASH BEFORE EATING.

SECTION IX: SPECIAL PRECAUTIONS

Handling and Storing

KEEP IN COOL PROPERLY VENTILATED EXPLOSION PROOF AREA.

Other Precautions

KEEP AWAY FROM HEAT SPARKS, AND OPEN FLAMES. USE APPROVED GROUNDING
EQUIPMENT TO AVOID STATIC SPARKS.

NOTE: THIS PRODUCT CONTAINS XYLOL AND IS SUBJECT TO THE REPORTING
REQUIREMENTS OF SARA 313 AND 40 CFR 372

WARNING! This product contains chemical substance(s) known to the state of
California to cause cancer and birth defects or other reproductive harm.

DISCLAIMER: THE INFORMATION AND RECOMMENDATIONS SET FORTH HEREIN ARE
PRESENTED IN GOOD FAITH AND BELIEVED TO BE CORRECT AS OF THIS DATE.
EASTWOOD MAKES NO REPRESENTATION AS TO THE COMPLETENESS OR ACCURACY
THEREOF. INFORMATION IS SUPPLIED UNDER THE CONDITION THAT THE RECIPIENT
WILL MAKE HIS OWN DETERMINATION AS TO ITS SUITABILITY FOR THEIR
INTENDED PURPOSE, PRIOR TO USE.

=====
END OF MSDS
=====