

EASTWOOD DIAMOND CLEAR® FOR BARE METAL SURFACES is the ideal top coat to protect and preserve metal surfaces. Use over unfinished or polished surfaces to protect from corrosion and ultra-violet light. Withstands temperatures up to 300°F. One can covers about 6-8 square feet.

DIRECTIONS – READ ALL INSTRUCTIONS BEFORE USING THIS PRODUCT

1. Clean part thoroughly. Remove wax, grease, oil, buffing compounds, etc. Use Eastwood PRE Painting Prep #10041Z.
2. For best results, use when can and surface temperature are between 70°-90°F (21°-32°C) and humidity is 50% or lower.
3. Shake can vigorously for at least 1 minute before and occasionally during use. Hold can approximately 12" from surface. Use even, overlapping strokes. Apply several thin, even coats allowing 15 minutes dry time between each coat. For best protection and durability, make sure you have complete coverage on the entire piece.
4. Allow surface to completely dry 24 hours before handling.
5. If clogging develops, turn spray button 1/4 turn. If clogging persists, remove and clean button with suitable solvent. Do not stick pin or sharp object into can opening.
6. Discard empty can according to Federal, State, and Local regulations. Do not place in home garbage compactor.

IMPORTANT: To prevent clogging, after each use, invert the can and spray a few short blasts to clear the valve.

CONTAINS: Acetone (CAS #67-64-1), Dimethyl Ether (CAS #115-10-6), Aromatic Solvent (CAS #64742-95-6), Resin (Trade Secret), Propane (CAS #74-98-6), Toluene (CAS #108-88-3) and Aromatic Solvent (CAS #64742-94-5).

DANGER: CONTENTS EXTREMELY FLAMMABLE AND UNDER PRESSURE.

Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F. Harmful or fatal if swallowed. Use only with adequate ventilation. Irritating to skin and eyes. Sensitizing to the skin.

WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

FIRST AID: In case of eye contact, flush thoroughly with water for 15 minutes and get medical attention. For skin contact, wash with soap and water. If overcome by vapors, remove to fresh air. If swallowed, do not induce vomiting, contact physician immediately.

VOC CONTENT: CCP Maximum MIR 1.5

KEEP OUT OF THE REACH OF CHILDREN

**Only in the Event of a Chemical Emergency Involving A Spill, Leaks, Fire, or Exposure Call Chemtrec Toll Free Day or Night:
1-800-424-9300 International Call Collect: (202) 483-7616**

Manufactured for The Eastwood Company
263 Shoemaker Road, Pottstown, PA 19464
USA: 1-800-345-1178 Canada: 1-800-820-9042
International: (610) 323-2200 www.eastwood.com
© Copyright 2013 Easthill Group, Inc.



Scan for product info



DO THE JOB RIGHT.

DIAMOND CLEAR®

GLOSS FINISH FOR BARE METAL



- Provides High Gloss Protection
- Compatible With All Metals
- Heat Resistant Up To 300°F

DANGER:
CONTENTS EXTREMELY FLAMMABLE AND UNDER PRESSURE.
Harmful or Fatal if Swallowed. Irritating to the skin and eyes.
Vapor Harmful. Read Precautions On Rear Panel Before Use.

Net wt. 11 oz. / 312 grams

10200 Z